

VOIP Gateway

Model IPGate-2000

WaveTramp's WT-IPGate-2000 VOIP gateway product series can route your voice and fax communications into IP network, therefore significantly reduce the inter-office long distance communication cost. The products are primarily designed for small and medium size business.

Key Features

- High quality Voice/Fax
- High security settings
- PPP/PPPoE, DHCP Client
- Static/Dynamic IP
- Billing Interface
- NAT/Firewall
- Basic PBX function
- Remote management

Specifications

- SIP, MGCP
- 2 or 4 RJ45 (WAN/LAN)
- 2-16 FXS/FXO
- G.711/G723.1/G.729A (Voice)
- T.38 (FAX)
- NAT
- DTMF signal
- Caller ID
- Management(Telnet/Web/SNMP)
- Power: 100-240 V
- Weight: 1kg/3kg/6kg
- Temperature : 0-40 °C
- Humidity : <95%

Model	FXO/FXS	WAN/LAN
WT-IPGate-2002	2	1/3
WT-IPGate-2004	4	1/1
WT-IPGate-2008	8	1/4
WT-IPGate-2016	16	1/4



WaveTramp Technologies, Inc
Shenzhen, China
Phone: +86-755-2601-4880 (China)
Phone: +1-781-218-3078 (USA)
Fax: +86-755-2601-4880x8815
Email: sales@wavetramp.com
<http://www.wavetramp.com>